


DS-K2700X Series

Access Controller

Professional control, flexible management



Access Module
DS-K27002X

Main Controller
DS-K2701X, DS-K2702X, DS-K2704X

Meet Hikvision's Professional Access Controller

Hikvision's flagship DS-K2700X series access controller is specially designed to provide you with professional multi-door control with flexible management, ensuring seamless security & control solutions for a wide range of high-capacity access applications.



**MAX. 128
Doors control**

(DS-K2704X with 62 access modules)



100,000 Users



600,000 Events



Easy installation



**Multiple
mngt. solutions**



**Advanced
access control
applications**

Easy web management



Requiring no software configuration via **device web** interface



Step-by-step **wizard** for easy operation



Quick **navigation bar** for access configurations and event search

Event Search: by unlocking methods, time, personnel, etc.

Access Point Management: via visualized topology

Configuration: single door setting, like areas, unlocking time, etc.

Access Control Management

Default Area

Access Point Controlled

Access Module	Online	Offline
Total: 2	2	0

Card Reader	Online	Offline
Total: 8	0	8

Quick Start


Add Person Add Device

Event

Empl...	Name	Card ...	Door
---------	------	----------	------


RS-485 cascading for multi-door control

- **RS-485 cascading** to control **max. 128** doors
(with 62 access modules)



Up to 16 access modules can be connected.

- **RS-485 redundant protection** for **max. 68** doors
(with 32 access modules)





Up to 16 access modules can be connected.

* Without RS-485 cascading, DS-K2700X supports 1/2/4 door control

Advanced access control


Applications

1 **Multi-door Interlocking**
Supports *up to 32* interlocking doors.



2 **Anti-passback**
Support *up to 32 routes*


3 **First Person in**



4 **Multi-factor Authentication**
Support up to *8 authentication levels*

PoE power supply

Standard PoE power supply to power the device and lock directly, for added convenience




*Note: Only DS-K2702WX-E1(P) & DES-K270wWx-E1 support PoE power supply now, supporting max. 2 doors

Easy to install and use


 Flexible installation options

 Backup battery for enhanced convenience

DIN rail mounting



Wall mounting



Backup Battery

Recommended for use in scenarios where power is easily disconnected

Battery model 7Ah

Dimensions 151 mm x 94 mm x 65 mm

Support charging and discharging

*Models that support backup battery: DS-K2701/2/4/8X, DS-K2702WX-E1

Product Showcase

Main Board



DS-K2701X(P)



DS-K2702X(P)



DS-K2704X(P)



DS-K2702WX-E1(P)

Controller with Enclosure



DS-K2701/2/4X




DS-K2702WX-E1



DS-K2708X*

*Note: Cables & backup battery are not included in the product.

Access Module



DS-K2M002X



www.hikvision.com
support@hikvision.com

